

Power Specification

DC Output:	Output Power: T124: 120 kW T184: 180 kW
	Dynamic Power Sharing: T124: 60 kW power granularity T184: 90 kW power granularity
	Output voltage: 150 - 920 V
	Output current (peak): CCS: 400 A; J3400/NACS: 375 A
	Number of outlets: single, dual; (CE): dual + AC socket
	Total system efficiency: (CE): up to 95.6 % (NA): up to 96 %

AC Input:	Nominal voltage: (CE): 400 V ($\pm 10\%$) (NA): 480 Y / 277 V ($\pm 10\%$)
	Nominal input current (RMS): T124: (CE): 187 A / 220 A (NA): 153 A T184: (CE): 280 A / 312 A (NA): 230 A
	Frequency: (CE): 50 Hz ($\pm 10\%$) (NA): 60 Hz ($\pm 10\%$)
	Earthing systems: TN-S, TN-C, TN-C-S, TT (with upstream RCD)
	Inlet cable size per phase: up to 180 mm ²
	Power factor: > 0.99 @ full load
	Total Harmonic Distortion (THD): < 4.5 % @ full load
	Overvoltage category: III SPD: Type 2

System Specification

Operating Conditions:	Operating from (CE): -35 °C to 50 °C (NA): -31 °F to 131 °F (with derating) Storage / transport from -5 °C to 40 °C (23 °F to 104 °F)
	Altitude: up to 2000 m (6562 ft) Humidity: up to 95 %, non-condensing
	Impact resistance: IK10 (HMI: IK08) IP rating: IP54
	Noise emission: < 65 dB(A) @ 1 m front door, 25 °C (77 °F), full power Intended use: indoor and outdoor Mounting options: floor mounted Environment pollution degree: Class 3 (outside), Class 2 (inside)
Dimensions:	H x W x D: 1900 x 565 x 880 mm (74.8 x 22.2 x 34.6 in) Weight: T124: 445 kg (981 lbs) T184: 475 kg (1047 lbs)
	Accessibility: meets ADA requirements for height, reach, and user interface

Customer Interface

Display:	Type: 7" LCD; Interface: Touchscreen
Lighting:	Gun holder: LED
Languages:	English (others available via software upgrade)
Connector Options:	Patented two-phase cooling technology (CCS1, CCS2), Air-cooled J3400 (NACS); (CE): AC socket
Cable Management System (CMS):	Optional cable retraction CMS
Cable:	(CE): Length: 5 m (16.4 ft); Reach with CMS: 3.5 m (11.5 ft) (NA): Length: 6 m (19.7 ft); Reach with CMS: 5 m (14.4 ft) Further options available, Type: Air-cooled
Authentication Methods:	RFID, Autocharge, Plug and Charge, Option: payment terminal for credit/debit card
RFID System:	Mifare ISO 14443 A/B to part 4 and ISO/IEC 15693. Others available on request (NFC, Calypso, Ultralight, PayPass, and more)
Remote Management:	Access control, configuration, diagnostics, software updates

Standards & Compliance

Safety Standards:	(CE): EN IEC 61851-1: 2019, EN IEC 61851-23: 2014/AC: 2016, EN IEC 62311: 2020 (NA): UL2202
Metering:	(CE): Eichrecht (NA): CTEP/NTEP
EMC:	(CE): Class A according to: IEC 61851-21-2: 2018, EN IEC 61000-6-1: 2007, EN IEC 61000-6-2: 2019, EN 61000-6-3: 2007+A1: 2011, EN 61000-6-4: 2007+A1: 2011, ETSI EN 301 489-1 v2.2.0: 2017 (NA): Class A (90-180 KW), 47CFR FCC Part 15b; ENERGY STAR® certified; ICES 003
Manufactured:	USA & Europe
Network Connections:	Cellular: LTE Cat 4/UMTS/GSM, Ethernet: 10/100 Base-T
Network Communication Protocol:	(CE): OCPP 1.6J (NA): OCPP 1.6J Core and Smart Charging Profiles; OCPP 2.0.1 Core; Autocharge via OCPP
Vehicle Communication Protocol:	DIN 70121, ISO 15118, Autocharge
Short Circuit Current Rating:	(CE): 25 kA (NA): 65 kA
RED Directive:	EN 300 330 V2.1.1: 2017, EN 301 908-13 V13.2.1: 2022, EN 50364: 2020, EN 62311: 2020, EN 301908-2 V11.1.2: 2017
Additional Standards:	T124 T184: IEC 62196-2, IEC 62196-3, OCA 1.6J (Feb 2024) T184: NEVI configuration: FHWA Build America, Buy America