



## Product Specifications

Description	Specifications
<b>EVSE Level</b>	AC Level 2
<b>Connector Type</b>	SAE J1772 (Type 1)
<b>Max Output Rating</b>	40A; 9.6 kW Maximum Output – For use with 50A Circuit Rating
<b>Alternate Adjustable Output Ratings</b>	32A; 7.68 kW Maximum Output – For use with 40A Circuit Rating 24A; 5.76 kW Maximum Output – For use with 30A Circuit Rating 16A; 3.84 kW Maximum Output – For use with 20A Circuit Rating
<b>Charge Cable Length</b>	18 ft. (5.5m) for GR1-6-18-XX and GR1-14-18-XX 24 ft. (7.2m) for GR1-6-24-XX and GR1-14-24-XX
<b>Electrical Circuit / Input Power Requirements</b>	Dedicated 208VAC Single Phase or 240VAC Split Phase, 50/60 Hz.; Branch Breaker: Double pole; Circuit Conductors: Line 1, Line 2, Earth / Ground
<b>Input Power Connection</b>	Standard: Plug-in, NEMA 6-50 or NEMA 14-50 Plug. Plug is removable for Hardwire Connection.
<b>Installation Rating</b>	NEMA 4, Indoor/Outdoor Rated
<b>Operational Ratings</b>	Temperature: -22°F to 122°F (-30°C to 50°C); Humidity: 95% RH non-condensing
<b>Overall Dimensions</b>	EVSE: 10.25 x 6.25 x 3.75 inches (26.0 x 16.0 x 9.3 cm)
<b>Display &amp; Indicators</b>	LED Charge Status Indicators (Power/Ready, Charging, Fault)
<b>Cable Management</b>	EasyEvPlug™ with cable management
<b>Standards &amp; Compliance</b>	UL Certified. E510712. Energy Star Certified.