



HEVC19 Level 2 Up to 48A



Ultra slim design with pure PC,
Anti-UV treatment & yellow resistance



IK08 & Type 3 enclosure for
indoor & outdoor use



48A to 16A by switch



Specified screws and tool for security



Model 1: Plug & Charge



Model 2:
Wi-Fi & Bluetooth + APP control




Model 3:
OCPP 1.6J with core function



Type 1 plug with 18ft cable

SCAN
ME



HWISEL^{EV}

Model No.	HEVC19/32AC	HEVC19/40AC	HEVC19/48AC
Input Voltage	208-240Vac		
Frequency	50-60Hz		
Amperage	32A	40A	48A
Max. Power Output	7.6kW	9.6kW	11.5kW
Net Weight	9.5lbs	12.0lbs	13.1lbs
Gross Weight	12.0lbs	14.4lbs	15.5lbs
Product Dimensions	7.1" x 7.1" x 3.7"		
Package Dimensions	17.7" x 17.7" x 6.3"		
Protection & Standard			
Charging Interface	SAE J1772 Compliant, Type 1 Plug		
Safety Compliance	UL2594, UL2231-1/-2		
Multiple Protection	UVP, OVP, RCD (CCID 20), SPD, Ground Fault Protection OCP, OTP, Control Pilot Fault Protection		
Environmental			
Operating Temp.	-30° C to 50° C		
Relative Humidity	Up to 95% non-condensing		
Cable Length	18ft Standard (25ft Optional with Surcharge)		

CONTACT US:



1-800-775-5759



info@hwisel.com



hwisel.com